

Unit 7, Sabre Buildings, Sabre Close, Heathfield Industrial Estate,

Newton Abbot, Devon. TQ12 6TW

Email: info@belvedereproducts.co.uk

Web: www.belvedereroofs.co.uk

STRATUS Roof Enquiry Form

QUOTE or ORDER

Delivery Date:

Company Name:


Contact Name:

Reference:


Site Post Code:

Signed by:





See Important Notes Below regarding dimensions



Length:

Width:

Roof Colour Roof Glazing Notes: External Internal Tough/Argon/Tough -Warm Edge (4/16/4) Aluminium **Unglazed** White (9016) Activ Sun Shade Blue (u1.0) Grey (7016) Activ Blue Tint (u1.2) RAL No. **Activ Neutral Tint (u1.2)** Activ Aqua Tint (u1.2) Clear Low 'E' (u1.2) Anti Sun Bronze/K (u1.2) Anti Sun Artic Grey/K (u1.2) Celsius One Blue Tint (u1.0) **Celsius Clear Neutral Tint (u1.0) Celsius Elite Blue Tint (u0.9)**


Important Notes:

- 1. Set out is always measured to external face of timber kerb.
- 2. Timber kerb should be a minimum of 150 mm x 70 mm wide (not supplied).
- 3. Width up to 3000 mm. Length up to 6000 mm nominal sizes (4000 x 5851 Ext kerb sizes).
- 4. Fixed pitch of 20 degree all round.
- 5. Double ended hipped (rectangle shape). supplied without any Finial or Decorative Cresting's
- 6. Supplied glazed or unglazed for 24 mm sealed units glazing overhangs, no gutter.
- 7. Aluminium External Glazing Bar Capping's and Castings
- 8. All Lantern Roofs are supplied with PVC-U Internal Glazing Bar Capping's

Disclaimer:

The builder/installer is responsible for providing / checking structural timber deck. Building Regulation applications MAY be needed depending upon application. In certain commercial applications, restrictions in the use of the product may apply.





STRATUS Roof Enquiry Form